

i-scrub[™] 21B

Small effort. Big impact.



INQUIRE. INNOVATE. INSPIRE

Save time with mechanical scrubbing

Double disc action with the flexibility to even scrub areas in a vertical position. Equipped with an adjustable head & 360° of free-range motion. With a powerful engine that achieves 400 RPM using two discs, it's a brilliant machine that allows the user to scrub any surface with extreme power. You can manually dose your solution with the push of a button. Easily convert your machine into a handheld unit for polishing, powered by Li-ion battery technology for the same power.

360 degrees of motion

The adjustable head can rotate in 360° and is so flexible you can clean at any angle, may it be horizontal or vertical. Start scrubbing everywhere and anywhere.

Key features



Dual brush heads

We have equipped the i-scrub 21B with two brush heads, for higher mechanical power and cleaning narrow gaps in sturdy areas.

Centralized controls

The in height adjustable telescopic wand is easily controlled at the grip. All of your actions, switches and controls are within the reach of your fingertips.



Manually dose

You can manually dose your solution to your satisfaction with the push of a button. Get your areas clean on your own terms.

Bag your equipment & keep it together

Technical specifications

O LET

| Weight i-scrub 21b | 3.2 kg |
|------------------------------------|-----------------------------------|
| Weight i-scrub 21b handy | 2.2 kg |
| Weight i-scrub 21b handy + case | 4.2 kg |
| Size i-scrub case (I x w x h) | 40 x 36 x 11 cm |
| Size i-scrub 21b (l x w x h) | 15x 25 x 915~1270 mm |
| Size i-scrub 21b handy (I x w x h) | 22 x 9 x 15 cm |
| Power | 25W |
| Drive voltage | 12 V DC |
| Voltage charger | Available in 110, 115, 230, 240 V |
| Power source | i-power 7 battery* |
| Battery spec. | 14.4 V 6.6 Ah |
| Running time Li-ion | 150 minutes |
| Charging time Li-ion | 210 minutes |
| Brush speed | 400 RPM |
| Noise level W/O pump | 72 dB |
| Noise level W/T pump | 73 dB |
| Scrub area | 21 cm |
| Minimal clearance area | 95 mm |
| Material | ABS |



i-teamglobal.com